PRODUCT DATA



FASSON® High Gloss Board FSC® Certified

Issued July 2024

Introduction

A self-adhesive paper sheet product for offset printing.

Description

Face: A premium-quality cast-coated woodfree paper, mirror-finished glossy surface,

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Availability

Backing U	Adhesive 3	Supertack
No cracklines		X

Printing & Conversion

Offset printing.

Before applying the label, the surface must be clean, dry and grease-free.

Recommendations for use

High-quality multi-colour print jobs where a stiff face material is an advantage, e.g. swatch/colour cards, postcards and puzzles.

For indoor use.

General

Shelf life: 2 years stored at 20°C / 55% R.H.

Total caliper (±10 %): 293 micron

For information regarding EHS regulation, please visit our website under downloads "Technical bulletins" TB 7.8 Product Compliance Fasson Offset" and for technical guidance "Technical bulletins" – Offset printing.



FASSON® High Gloss Board FSC® Certified

PRODUCT CHARACTERISTICS

Physical properties

Face

Basis weight:	180g/m^2	ISO 536
Caliper:	186 micron	ISO 534
Tensile:	6.5 kN/m MD / 3.6 kN/m CD	ISO 1924/2
Brightness ISO:	88 %	ISO 2470/2
Opacity:	99 %	ISO 2471

Adhesive

Supertack: A water-based permanent adhesive specially developed for apolar and rough

surfaces. High initial tack combined with strong permanent bond.

Supertack

Adhesion (N/25mm) (FTM 1 on steel/20 min. bond time) 17.2 Tack(N) (FTM9 on st.steel) 11 Minimum application temperature +5 Service temperature range after 24 hrs (°C) +80 Resistance to cold (°C)¹⁾ down to -20

Backing

No cracklines: A bleached one-side-coated white kraft, especially designed for sheet products, featuring minimal moisture sensitivity

Basis weight: 86 g/m² ISO 536 87 micron ISO 534 Caliper:

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Guarantee and liability:
All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see https://www.lecta.com/terms

Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.



¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.